




## Bathroom sponge 1/1

## B201

<b>BRAND, PRODUCT NUMBER AND NAME</b>	BONUS	B201	BATHROOM SPONGE 1/1
<b>TARIC</b>	3924900090		
<b>PRODUCER/DISTRIBUTOR</b>	Bonus Kft. 7800 Siklós, Ipartelepi út 2., Magyarország +36 1 770 7000 info@bonus-hungary.com		
<b>CERTIFICATES</b>	MSZ EN ISO 9001:2015, MSZ EN ISO 14001:2015, MSZ 45001:2018		
<b>STORAGE</b>	Store in a dry, clean place. Keep away from fire and direct sunlight.		
<b>PRODUCT PACKAGING</b>	30 mikron thick, mirror-printed BOPP foil		
<b>OUTER CASE</b>	Recyclable, FC243-55 LDPE bag and foil		
<b>COMPOSITION</b>	20 kg/m <sup>3</sup> polyurethane foam, 550g/m <sup>2</sup> non-scratch scourer		
<b>TRADEMARK</b>			
<b>PRESS KIT</b>	<a href="https://img.bonus-hungary.com/products/B201/B201.zip">https://img.bonus-hungary.com/products/B201/B201.zip</a>		
<b>TERMÉK WEBOLDALA</b>	<a href="https://bonustakaritoeszkozok.hu/termek/furdoszoba-szivacs/">https://bonustakaritoeszkozok.hu/termek/furdoszoba-szivacs/</a>		

LOGISTICS DETAILS	1×	1×		
	PIECE	PACKAGE	OUTER CASE	PALETTE
		SALES UNIT	ORDER UNIT	
<b>PIECES</b> <i>UNITS</i>	1 PIECE	1 PIECE	36 PACKAGE	3 024 PACKAGE
<b>NET WEIGHT</b> <i>GROSS WEIGHT</i>	13 g	11,5 g 13 g	0,468 kg 0,66 kg	55,44kg
<b>DIMENSIONS</b> 	12×6,5×5cm	12×6,5×5cm	40×20×21cm	120×80×230cm
<b>EAN-13</b>	-	5997844304201	5997844304225	-

SPONGE COMPOSITION AND PROPERTIES	UNIT	TEST PROCEDURE	VALUE
NOMINAL FOAM DENSITY	kg/m <sup>3</sup>	PN-EN ISO 845: 2000	20 – 23
NOMINAL HARDNESS CLD (40%)	kPa	PN-EN ISO 3386-1: 2000	3,65 - 4,50
RESISTANCE MINIMUM	%	PN-EN ISO 8307: 2000	3
COMPRESSION (50%) MAXIMUM	%	PN-EN ISO 1856: 2004	7
TENSILE STRENGTH MINIMUM	kPa	PN-EN ISO 1798: 2001	100
TENSION STRENGTH MINIMUM	%	PN-EN ISO 1798: 2001	150
CERTIFICATION	<ol style="list-style-type: none"> <li>Oeko-Tex Certificate Standard 100, Kl. I</li> <li>ÉMI-TÜV Dissolution test R-1349209/1</li> </ol>		
COMPOSITION	Flexible polyether-polyurethane foam block made with Maxfoam or Novaflex® process.		


FOAM PROPERTIES	TOLERANCE	VALUE	UNIT
FOAM DENSITY	kg/m <sup>3</sup>	PN-EN ISO 845: 2000	23 – 26
COMPACTION (50%) MAXIMUM	kPa	PN-EN ISO 1856: 2004	7

## SCOURER LAYER INGREDIENTS

<b>COMPOSITION</b>	POLYESTER AND POLYAMIDE FIBERS
<b>BINDING RESIN</b>	VINYL-ACRYLIC RESIN
<b>SCOURING MATERIAL</b>	MINERAL GRAINS
<b>COLORANTS</b>	NATURAL – NON-TOXIC
<b>USAGE</b>	HOUSEHOLD
<b>ADDITIVES</b>	DOES NOT CONTAIN

SCOURER LAYER PROPERTIES	TOLERANCE	VALUE	UNIT
<b>WEIGHT</b>	± 5%	550	g/m <sup>2</sup>
<b>THICKNESS</b>	± 1 mm	6,5	mm

SCOURER LAYER PERFORMANCE	TOLERANCE	VALUE	UNIT
<b>TENSION STRENGTH Y DIRECTION</b>	± 4%	115	N/cm <sup>2</sup>
<b>TENSION STRENGTH X DIRECTION</b>	± 4%	130	N/cm <sup>2</sup>
<b>SCOURING EFFECT</b>		≥270	mg

<b>MADE BY</b>	<b>APPROVED</b>
SÁGI NORBERT 2023.08.04. 	BOTOS ANDREJ 2023.08.04. 